


FORO BANCO - COUNTER HOLE

tolleranza consigliata - suggested tolerance



Codice - Item	a [mm]	b [mm]
ZBX11	442 ^{+1 0}	305 ^{+1 0}
ZBX12	442 ^{+1 0}	404 ^{+1 0}
ZBX13	442 ^{+1 0}	442 ^{+1 0}
ZBX14	502 ^{+1 0}	442 ^{+1 0}

Codice - Item	a [mm]	b [mm]
ZBX15	602 ^{+1 0}	442 ^{+1 0}
ZBX16	442 ^{+1 0}	502 ^{+1 0}
ZBX17	442 ^{+1 0}	602 ^{+1 0}
ZBX18	442 ^{+1 0}	702 ^{+1 0}


Se il foro banco non rispetta le misure provvedere a spessorare con legno.

Should the counter hole slightly differ from the dimensions stated in the above table, reinforce the counter with appropriate wood crosspieces.


MONTAGGIO - ASSEMBLING PROCESS

1


FISSARE LE CERNIERE
FIX THE HINGES


2


AUTOCENTRAGGIO SPORTELLO
DOOR SELF-TRUE UP PROCESS


3

FISSARE IL LATO OPPOSTO CERNIERE
FIX THE OPPOSITE HINGES SIDE


4

FISSAGGIO FINALE
FINAL FIXING



TUTTE LE VITI INCLUSE Testa svasata piana 3,9 x 25 mm

ALL SCREWS INCLUDED Countersunk flat tapping 3,9 x 25 mm

