


## FORO BANCO - COUNTER HOLE

tolleranza consigliata - suggested tolerance



Codice - Item		a [mm]	b [mm]
AX11	AX51	442 <sup>+1</sup> <sub>0</sub>	305 <sup>+1</sup> <sub>0</sub>
AX12	AX52	442 <sup>+1</sup> <sub>0</sub>	404 <sup>+1</sup> <sub>0</sub>
AX13	AX53	442 <sup>+1</sup> <sub>0</sub>	442 <sup>+1</sup> <sub>0</sub>
AX14	AX54	502 <sup>+1</sup> <sub>0</sub>	442 <sup>+1</sup> <sub>0</sub>


Codice - Item		a [mm]	b [mm]
AX15	AX55	602 <sup>+1</sup> <sub>0</sub>	442 <sup>+1</sup> <sub>0</sub>
AX16	AX56	442 <sup>+1</sup> <sub>0</sub>	502 <sup>+1</sup> <sub>0</sub>
AX17	AX57	442 <sup>+1</sup> <sub>0</sub>	602 <sup>+1</sup> <sub>0</sub>
AX18	AX58	442 <sup>+1</sup> <sub>0</sub>	702 <sup>+1</sup> <sub>0</sub>

Se il foro banco non rispetta le misure provvedere a spessorare con legno.


Should the counter hole slightly differ from the dimensions stated in the above table, reinforce the counter with appropriate wood crosspieces.

## MONTAGGIO - ASSEMBLING PROCESS


### 1 FISSARE LE CERNIERE FIX THE HINGES




### 2 AUTOCENTRAGGIO SPORTELLO DOOR SELF-TRUE UP PROCESS



### 3



### 4 FISSAGGIO FINALE FINAL FIXING



**VITI PER LE CERNIERE (include)** Testa svasata piana  
nichelata 3,9 x 25 mm

**SCREWS FOR THE HINGES (included)** Countersunk  
flat tapping nickel chromed screw 3,9 x 25 mm



**VITI DA UTILIZZARE PER LA CORNICE (non include)**  
autofilettante testa mezza tonda 3,5 x 32 mm

**SCREWS TO BE USED FOR THE FRAME (not included)**  
flat head tapping screw 3,5 x 32 mm




## SOLO PER AX5

## - ONLY FOR A5

### SPORTELLLO CON SERRATURA :

FISSARE LA STAFFA CON LE 2 VITI IN  
DOTAZIONE

**DOOR WITH LOCK** : LOCK BRACKET FIXING  
WITH 2 INCLUDED SCREWS




VITI include  
SCREWS included

### SPORTELLLO CON SCROCCO :

FISSARE LA STAFFA CON LE 2 VITI IN  
DOTAZIONE

**DOOR WITH LATCH** : LATCH BRACKET FIXING  
WITH 2 INCLUDED SCREWS



VITI include  
SCREWS included