






FORO BANCO - COUNTER HOLE


tolleranza consigliata - suggested tolerance

Codice - Item	a [mm]	b [mm]
AV16	442 ⁺¹ / ₀	502 ⁺¹ / ₀
AV17	442 ⁺¹ / ₀	602 ⁺¹ / ₀
AV18	442 ⁺¹ / ₀	702 ⁺¹ / ₀

Se il foro banco non rispetta le misure provvedere a spessorare con legno.

Should the counter hole slightly differ from the dimensions stated in the above table, reinforce the counter with appropriate wood crosspieces.

MONTAGGIO - ASSEMBLING PROCESS
1
FISSARE LE CERNIERE
FIX THE HINGES

2
AUTOCENTRAGGIO SPORTELLLO
DOOR SELF-TRUE UP PROCESS

3

4
FISSAGGIO FINALE
FINAL FIXING

VITI PER LE CERNIERE (include) Testa svasata piana nichelata 3,9 x 25 mm

SCREWS FOR THE HINGES (included) Countersunk flat tapping nickel chromed screw 3,9 x 25 mm

VITI DA UTILIZZARE PER LA CORNICE (non include) autofilettante testa mezza tonda 3,5 x 32 mm

SCREWS TO BE USED FOR THE FRAME (not included) flat head tapping screw 3,5 x 32 mm
